

类型 Type	冷媒	系列 Series	型号 Model	排量 Displ.	制冷量 Capacity		功率 Power	能效比 COP	频率范围 f Rang	外形尺寸 Outside Dimensions					
				(Cm ³ /rev)	W	BTU/H	W	W/W	Hz	A(mm)	B(mm)	C(mm)	D(mm)	E(mm)	F(mm)
DC	R22	X1	DH108X1C-20FZD3	10.8	2240	7638	590	3.80	18~120	266	246	109	80	φ8.2	φ12.9
			DH130X1C-20FZD3	13.1	2695	9190	700	3.85	18~120	266	246	109	80	φ8.2	φ12.9
	R410A	X1	DA89X1C-23FZD	8.9	2650	9037	680	3.90	18~120	255	245	109	80	φ8.1	φ12.9
			DA89X1C-20FZ3	8.9	2650	9037	705	3.76	18~130	255	245	109	80	φ8.1	φ12.9
			DA108X1C-20FZ3	10.8	3200	10912	855	3.74	18~120	279	249	109	80	φ8.1	φ12.9
AC	R22	X1	BH108X2C-20FZ	10.8	2250	7673	725	3.10	30~120	266	246	109	80	φ8.2	φ12.9
			BH130X2C-20FZ	13.1	2700	9207	870	3.10	30~120	266	246	109	80	φ8.2	φ12.9
		X2	BH160X2C-20FT	16.2	3420	11662	1100	3.11	30~120	292	244	115	80	φ9.8	φ12.9
			BH200X2CS-20KU	20.0	4245	14475	1360	3.12	30~120	314	318	115	80	φ9.8	φ12.9
			BH240X2CS-20KU	23.9	5120	17459	1640	3.12	30~120	314	318	115	80	φ9.8	φ12.9
	R407C	X1	BG108X1C-20FZ	10.8	2340	7979	750	3.12	30~120	266	246	109	80	φ8.2	φ12.9
			BG130X1C-20FZ	13.1	2775	9463	890	3.12	30~120	266	246	109	80	φ8.2	φ12.9
		X2	BG200X2CS-20KU	20.0	4365	14885	1410	3.10	30~120	314	318	115	80	φ9.8	φ12.9
			BG240X2CS-20KU	23.9	5265	17954	1700	3.10	30~120	314	318	115	80	φ9.8	φ12.9
			R410A	X2	BA160X2CS-20KU	16.0	4750	16198	1640	2.90	30~120	321	315	115	80

